


## Spindle Lubricating Machine

### SL3 with 3 tank




Oil Tank Capacity	Topping Tank	9 Litre
	Flushing Tank	23 Litre
	Fresh Oil Tank	13 Litre
Electric Motor	Single Phase, 1 HP (0.75 kW) Induction Motor 220 / 230V / 1425 RPM	
Weight	Net Weight - 110 kg	
	Gross Weight - 170 kg	

Note : Lubrication machine is also available for worsted / Jute spinning and texturizing



Flushing Gun for cleaning



Topping Gun For new oil

### Helping hand to save oil & life of Bearings in the Spindle Bolster

- Perfect Lubrication machine is for spindles to maintain bearing life for longer period
- The machine is provided with 3 Oil Tanks
- The flushing and filling of oil to the Bolsters is done by two different special oil Guns
- One gun is for flushing and the other one is for topping
- Flushing gun is fitted with flushing and sucking tube used for flushing, bearing and sucking flushed oil from the spindle bolster
- The delivery of Topping gun is meant for filling fresh oil into the Bolster. It is calibrated one
- The calibration can be adjusted by screw to the required quantity of oil to be filled in to the different size of bolster
- Since the machine is compact, it is easy to move even in narrow alley between Ring-Frames
- It works with 230V A.C. Single phase
- Power 0.75 kW